CP-019 - CPU Units (Built-in EtherNet/IP)



Spare Part Number: CP-019

Net Weight: 190.00g

Net Dimensions: 90.00mm x 75.00mm x

62.00mm

Technical Datasheet: Protected Link

Manual: Protected Link

Description

CP-019 CPU Units with Built-in EtherNet/IP

component need to be programmed in the factory according to Equipment Type, Model and Serial Number)

CPU with built-in EtherNet/IP port, 20K steps program, 32K words data memory, 32K words x 1 bank EM, 2560 I/O max, option port for RS-232C/485, USB programming port, 3 expansion racks max.

NOTE: This component need to be programmed in the factory according to Equipment Type, Model and Serial Number.

CJ2M-CPU33

Basic Specs

Item Enclosure Grounding CJ2M-CPU3[]
Mounted in a panel
Less than 100?

CPU Unit Dimensions
Weight (see note 2)
Current Consumption
Operation

Environment

Ambient Operating

Temperature

Ambient Operating

Humidity condensation)

Atmosphere Must be free from corrosive

gases.

Ambient Storage - 20 to 70 °C (excluding

Temperature battery)

Altitude 2,000 m or less **Pollution Degree** 2 or less: Meets IEC

61010-2-201.

Noise Immunity 2 kV on power supply line

(Conforms to IEC

 $90 \text{ mm} \times 75 \text{ mm} \times 62 \text{ mm}$

190 g or less (see note 1)

10% to 90% (with no

5 VDC, 0.7 A

0 to 55 °C

61000-4-4.)

61010-2-201.

Zone B

EMC Immunity Level

Vibration Resistance Conforms to IEC60068-2-6

5 to 8.4 Hz with 3.5-mm amplitude, 8.4 to 150 Hz Acceleration of 9.8 m/s² for 100 min in X, Y, and Z

directions

(10 sweeps of 10 min each =

100 min total)

Shock Resistance Conforms to IEC60068-2-27

147 m/s², 3 times in X, Y, and Z directions (100

m/s² for Relay Output Units) 5 years at 25 °C

Battery Life 5 years at 25 °C

Weight Approx. 10 g
Model CJ1W-BAT01

Applicable Standards Conforms to cULus, NK, LR,

and EC Directives.

Note:1. Without a Serial Option Board.

2. Includes wight of end covers and battery.

Equipment reference

Equipment Model Reference

Classic 3 P Classic 4 P

EVO 3 IP CJ2M Easy to Plate **EVO 3 IP D** CJ2M

Easy to Plate EVO 3 IP I CJ2M

EVO 4 IP

Easy to Plate EVO 4 IP D

Easy to Plate EVO 4 IP I

EVO 5 IP

Easy to Plate EVO 5 IP D

Easy to Plate EVO 5 IP I

611 V2 CPU CPU

620 CPU 621 CPU

830 CPU

Catalogues/Families

Suitable for the following equipment models:	
CLASSIC 3 P	
CLASSIC 4 P	

EASY TO PLATE EVO 4	
IPD	
EASY TO PLATE EVO 4	
IPI	
EASY TO PLATE EVO 5	
BPD	
EASY TO PLATE EVO 5	
BPI	
EASY TO PLATE EVO 5	
IPD	
EASY TO PLATE EVO 5	
IPI	
EVO 4 IP	
EVO 5 BP	
EVO 5 IP	
Spare Part Type	
Electrical Component	
Spare Part Group	
PLC	
Stock Type	
Standard Stock	

Product Gallery