

CR-009 - 3-conductor through terminal block

Product Code: CR-009

Weight: 11.90g

Dimensions: 7.50mm x 73.30mm x 32.90mm

Description

CR-009 3-conductor through terminal block

6 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 6,00 mm²; gray

WAG20061301

Specifications

Ratings per IEC/EN

Ratings per	IEC/EN 60947-7-1
Nominal voltage (III/3)	800V
Rated impulse voltage (III/3)	8kV
Rated current	41A
Rated current 2	57A
Legend (ratings)	(III / 3) ? Overvoltage category III / Pollution degree

Ratings per UL

Approvals per	UL 1059
Rated voltage UL (Use Group B)	600V
Rated current UL (Use Group B)	50A
Rated voltage UL (Use Group C)	600V
Rated current UL (Use Group C)	50A

Ratings per CSA

Approvals per	CSA 22.2 No 158
Rated voltage CSA (Use Group B)	600V
Rated current CSA (Use Group B)	50A
Rated voltage CSA (Use Group C)	600V
Rated current CSA (Use Group C)	50A

Equipment Ref
830 Ref **TB3, TB4**

812 Ref **TB1**

812 Ref **TB1**

Specification
Spare Part Type

Electrical Component	
Spare Part Group	
Others	
Stock Type	
Made to Order	

Product Gallery